Technical Information

No. 5606

Edition: 04/08 - subject to change

Substitutes: new Status: valid



XBO® 5000 W/H XL OFR

■ Product description

The OSRAM XBO® 5000 W/H XL OFR is a DC-operated lamp, developed with the latest high brightness technology for XBO lamps. The XL lamps, which stands for Xtreme life, are strictly optimized on performance and have an increased warranty up to 50%.

■ Technical data

Order reference	XBO® 5000 W/H OFR	
Rated lamp wattage	W	5000
Rated lamp voltage	V	35
Rated lamp current (=)	Α	140
Current control range	Α	100 - 150
Ignition voltage	kV_{s}	36
Min. open circuit voltage for cold / hot ignition	V	85 / 110
for cold / flot ignition	V	03 / 110
Luminous flux	lm	225000
Luminous intensity	cd	27000
Average luminance	cd/cm ²	95000
Luminous area wxh *)	mm	2.2 x 6.5
Electrode gap e (cold)	mm	7.5
Lamp length (overall) I ₁	mm	max. 424
Lamp length l ₂	mm	max. 380
LCL a	mm	167.5
Bulb diameter d	mm	70
Warranty	h	1200
Base - lamp sockets	Cathode Anode	SFaX 28-18 SFaX 30-16
Cable length I _c	mm	560

Lamp operation

Maximum permissible base temperature °C 230

Cooling Forced cooling / fan

Min. air flow velocity around discharge vessel m/s 6

Magnetic arc stabilization necessary for horizontal operation

Operating/burning position $s 15 \text{ (vertical } \pm 15^\circ \text{ ; anode up) ; p } 15 \text{ (horizontal } \pm 15^\circ \text{)}$



ф ф 9 2 $\underline{\circ}$ Ø ф

^{*)} w = luminance half width value; h = height of luminance area (corresponds to electrode gap, hot)